Stepan_®



Product Bulletin

Product Name

Chemical Structure

Chemical Description

CAS Registry No.

INCI Name

Applications

BIO-SOFT® S-101

n = 10.4 avg.

Linear Alkylbenzene Sulfonic Acid 68584-22-5

Dodecyl Benzene Sulfonic Acid

BIO-SOFT S-101 is an economical and versatile, biodegradable surfactant intermediate. This product can be neutralized with a variety of inorganic bases and organic amines to give a wide range of sulfonates with the properties of your choice. BIO-SOFT S-101 can be used to make both liquid and dry products, and left unneutralized, it is an effective surfactant in acidic environments. BIO-SOFT S-101 contains a minimum of sulfuric acid and upon neutralization produces material with little salt, light color and low odor, allowing wide latitude in formulating.

BIO-SOFT S-101 can be used in all types of household, industrial and institutional cleaners including laundry, dishwash, carwash, hard surface and general purpose detergents. It can also be utilized as an intermediate in preparation of emulsifiers and wetting and foaming agents. Unneutralized BIO-SOFT S-101 is an effective surfactant in acidic products such as liquid bowl, aluminum and dairy cleaners.

Neutralization Information: Temperature and pH must be controlled during neutralization of BIO-SOFT S-101 to prevent darkening of the product and corrosion of stainless steel equipment. The reaction temperature should not be allowed to exceed 50°C and the pH should not go below 6.5. Approximate amounts of BIO-SOFT S-101 and various alkalies for neutralization to make 100 lbs of active dodecylbenzene sulfonate are shown below. Actual requirements will vary with each shipment. Additional information is available on the neutralization and use of BIO-SOFT S-101 in a Stepan Technical Information Bulletin entitled "Neutralizing BIO-SOFT Acids".

Neutralization of BIO-SOFT S-101*

<u>Alkali</u>	BIO-SOFT S-101
25.6 lbs. NaOH (50%)	97.1 lbs.
38.2 lbs. KOH (45%)	92.7 lbs.
33.5 lbs. Triethanolamine (85%)	71.9 lbs.
40.7 lbs. Ammonium Hydroxide (28% NH3)	98.5 lbs.

*to obtain 100 lbs of LAS

Appearance	Dark, viscous liquid
pH, as is	
Actives (EW 318), % min	96
Pour Point, °C (°F)	
Freeze Point, °C (°F)	
Color, Klett (5% active sodium salt in water)	30 max.
Viscosity, cps at 5 °C	5,600
Viscosity, cps at 25 °C	890
Viscosity, cps at 50 °C	220
Flash Point (PMCC), °C (°F)	>94 (>201)
Density, g/ml (lbs/U.S. gal)	
RVOC, U.S. EPA, %	

Typical Properties

Oct. 2017 Supersedes; Jan. 2012 Page 1 of 2



Environmental **Effects**

Health Effects

Storage & Handling

Workplace Exposure

Clearances

Product Stewardship

Additional Safety Information

Oct 2017 Supersedes; Jan. 2012 Page 2 of 2

Product is readily biodegradable. Additional information is available upon request.

BIO-SOFT S-101 is slightly toxic orally (LD₅₀ = 500 - 2000 mg/kg) and when tested undiluted is corrosive to skin and eyes.

BIO-SOFT S-101 is a strong acid and should be handled with extreme care. Avoid contact with eyes and skin. Wash thoroughly after handling material.

Standard Packaging: BIO-SOFT S-101 is available in drums (475 lb, 215 kg) and in bulk quantities.

It is recommended that BIO-SOFT S-101 be stored in closed containers and kept in a cool, dry place. If material is frozen it should be heated gently and stirred to ensure it is homogeneous before use.

Bulk Storage Information: BIO-SOFT S-101 should be stored in vessels of 316 stainless steel or fiberglass with a corrosion liner. Heating and agitation are recommended for outside storage. Material should be stored between 80 - 100°F. An internal hairpin coil of 316 stainless steel with low pressure steam (under 50 psig) should be used if heating is required. Pumps, pipes and transfer lines should be 316 stainless steel.

Occupational exposure can occur primarily through skin contact or via inhalation of vapors and mists. Engineering controls, personal protective equipment, and other workplace practices should be used to control these exposures.

All components of BIO-SOFT S-101 are listed in the following countries; the registration numbers for the active ingredients are included in parentheses: United States (TSCA 68584-22-5), Europe (EINECS 271-528-9), Japan (ENCS 3-1907), Korea (ECL Serial No. KE-02595), Canada (DSL 68584-22-5), Australia (AICS 68584-22-5), Philippines (PICCS 68584-22-5), and China (IECSC 68584-22-5).

BIO-SOFT S-101 is also approved for use under 40CFR 180.910, 180.930, 180.940.

BIO-SOFT S-101 is available in Kosher grade.

BIO-SOFT S-101 meets the U.S. EPA Safe Choice Program's surfactant screen and is listed on www.cleangredients.org (an on-line database for green formulators). For further information, visit www.cleangredients.org. Additional Stepan ingredient listing can be found at www.stepan.com.

It is the responsibility of the formulator to review the chemical control regulations for each country where the end product is intended to be sold or used.

This product bulletin has been written in accordance with ACC's Product Stewardship guidelines.

A Safety Data Sheet is available upon request.



The information contained herein is based on the manufacturer's own study and the works of others and is subject to change without prior notice. The information is not intended to be all-inclusive, including as to the manner and conditions of use, handling, storage or disposal or other factors that may involve additional legal, environmental, safety or performance considerations. Nothing contained herein grants or extends a license, express or implied, in connection with any patents issued or pending of the manufacturer or others, or shall be STEPAN COMPANY MAKES NO construed as a recommendation to infringe any patents. PRODUCT WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR USE, EXPRESS OR IMPLIED, AND NO OTHER WARRANTY OR GUARANTY, EXPRESS OR IMPLIED, IS MADE, INCLUDING AS TO INFORMATION REGARDING PERFORMANCE, SAFETY, SUITABILITY, STABILITY, ACCURACY, COMPLETENESS, OR ADEQUACY. Stepan Company (and its employees, subsidiaries and affiliates) shall not be liable (regardless of fault) to the vendee, its employees, or any other party for any direct, indirect, special or consequential damages arising out of or in connection with the accuracy, completeness, adequacy, furnishing, use, or reliance upon information provided herein. The vendee assumes and releases Stepan Company (and its employees, subsidiaries and affiliates) from all liability, whether in tort, contract or otherwise to the fullest extent possible under the relevant law."

tepan

Corporate Headquarters Northfield, Illinois 60093, U.S.A. Phone: 847-446-7500

Fax: 874-501-2100

Website: www.stepan.com

For Technical Service Call: Stepan North America +1-800-745-7837 Stepan Mexico +55-11-5089-2208 Stepan Quimica +55-11-5089-2200 Stepan Colombia +571-636-2808

Stepan Europe +33-476-505-160 Stepan Asia +656-879-9855 Stepan Philippines +656-879-9855 For Customer Service Call: Stepan North America +1-800-457-7673 Stepan Mexico +52-555-533-1967

Stepan Quimica +55-11-5089-2200 Stepan Colombia +57-6-8993125 Stepan UK +44-161-338-5511 Stepan France +33-476-50-51-00

Stepan Philippines +63-2-842-7951