



Product Bulletin

BIO-TERGE® AS-40K

Product Name	
CAS Registry Number	68439-57-6
INCI Name	Sodium C ₁₄₋₁₆ Olefin Sulfonate
Applications	BIO-TERGE AS-40K is an aqueous solution of sodium olefin sulfonate which is produced by the continuous sulfonation of alpha olefins via Stepan's falling film process. Stepan's process minimizes the formation of disulfonates thereby offering a consistent high quality product. BIO-TERGE AS-40K is an ideal surfactant for a variety of detergent and personal care applications including hand soaps, shampoos, and bath products. It offers the formulator excellent viscosity and foam characteristics, as well as improved mildness over lauryl sulfates. It is more stable than alcohol sulfates over a broad pH range.
Typical Properties	<p>Appearance at 25 °C Clear liquid</p> <p>Actives (MW 315), % 39.2</p> <p>Unulfated Matter, % 0.68</p> <p>Sodium Chloride, % 0.27</p> <p>Sodium Sulfate, % 0.77</p> <p>pH, 10% aqueous 5.8</p> <p>Color (Klett, 5% active) 40</p> <p>Viscosity at 25 °C, cps 151</p> <p>Cloud Point (as is), °C (°F)..... 7 (45)</p> <p>Pour Point, °C (°F) -4 (25)</p> <p>Freeze Point, °C (°F)..... -7 (19)</p> <p>Flash Point (PMCC), °C (°F) >94 (>201)</p> <p>Boiling Point, °C (°F) >100 (>212)</p> <p>Density, g/ml (lbs/U.S. gal) 1.070 (8.9)</p> <p>Critical Micelle Concentration, mg/L 301</p> <p>RVOC, U.S. EPA, % 0</p> <p>Preservative Methylchlorisothiazolinone/Methylisothiazolinone</p>
Biodegradability	Product is readily biodegradable. A detailed biodegradability statement is available upon request.
Toxicity	BIO-TERGE AS-40K is slightly toxic orally (oral LD ₅₀ = 1.3-2.4 g/kg) and causes moderate skin and eye irritation at 10% active.
Storage & Handling	<p>Normal safety precautions (i.e., the use of gloves and safety goggles) should be employed when handling BIO-TERGE AS-40K. Contact with the eyes and prolonged contact with the skin should be avoided. Wash thoroughly after handling material. It is recommended that BIO-TERGE AS-40K be stored in sealed containers and kept at temperatures above 50 °F (10 °C). Avoid overheating or freezing. This material can gel and separate if exposed to cooler temperatures. Heat it slowly with mild agitation to insure its homogeneity before use.</p> <p><u>Bulk Storage Information:</u> Tanks made of 316 stainless steel or fiberglass with Atlac 382 corrosion liner are recommended. Positive displacement gear pumps and piping should be 316 stainless steel. Recommended storage for bulk tanks is 80-100 °F (27-38 °C).</p>



Clearances

Standard Packaging: BIO-TERGE AS-40K is available in bulk, 55 gallon drums and 275 gallon totes.

All components of BIO-TERGE AS-40K are listed in the following countries; the registration numbers for the active ingredients are included in parentheses: United States (TSCA 68439-57-6), Canada (DSL 68439-57-6), Australia (AICS 68439-57-6), Europe (EINECS 270-407-8), Korea (ECL Serial No. KE-32477), Philippines (PICCS 68439-57-6), and China (IECSC 68439-57-6). This product is approved for limited applications in Japan; please contact Technical Service for further details.

BIO-TERGE AS-40K is USDA authorized.

BIO-TERGE AS-40K is available as Kosher Certified.

BIO-TERGE AS-40K meets the U.S. EPA Safe Choice Program's surfactant screen and is listed on www.cleangredients.org (an on-line database for green formulators). For further information, visit www.cleangredients.org. Additional Stepan ingredient listing can be found at www.stepan.com.

It is the responsibility of the formulator to review the chemical control regulations for each country where the end product is intended to be sold or used.

Product Stewardship

This product bulletin has been written in accordance with ACC's Product Stewardship guidelines.

Additional Safety Information

A Safety Data Sheet is available upon request.



The information contained herein is based on the manufacturer's own study and the works of others and is subject to change without prior notice. The information is not intended to be all-inclusive, including as to the manner and conditions of use, handling, storage or disposal or other factors that may involve additional legal, environmental, safety or performance considerations. Nothing contained herein grants or extends a license, express or implied, in connection with any patents issued or pending of the manufacturer or others, or shall be construed as a recommendation to infringe any patents or to violate any applicable laws. STEPAN COMPANY MAKES NO WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR USE, AND NO WARRANTY OR GUARANTY OF ANY OTHER KIND, EXPRESS OR IMPLIED, IS MADE, INCLUDING REGARDING PERFORMANCE, SAFETY, SUITABILITY, STABILITY, ACCURACY, COMPLETENESS, ADEQUACY OR OTHERWISE. Stepan Company (and its employees, subsidiaries and affiliates) shall not be liable (regardless of fault) to the vendee, its employees, or any other party in respect of this information, including in respect of its accuracy, completeness, adequacy, furnishing, use, or reliance upon, and the vendee assumes and releases Stepan Company (and its employees, subsidiaries and affiliates) from all liability, whether in tort, contract or otherwise to the fullest extent possible under the relevant law.

Stepan 
Corporate Headquarters
Northfield, Illinois 60093, U.S.A.
Phone: 847-446-7500
Fax: 874-501-2100
Website: www.stepan.com

For Technical Service Call:
Stepan North America **+1-800-745-7837**
Stepan Mexico **+55-11-5089-2208**
Stepan Quimica **+55-11-5089-2200**
Stepan Colombia **+571-636-2808**
Stepan Europe **+33-476-505-160**
Stepan Asia **+656-879-9855**
Stepan Philippines **+656-879-9855**

For Customer Service Call:
Stepan North America **+1-800-457-7673**
Stepan Mexico **+52-555-533-1967**
Stepan Quimica **+55-11-5089-2200**
Stepan Colombia **+57-6-8993125**
Stepan UK **+44-161-338-5511**
Stepan France **+33-476-50-51-00**
Stepan Philippines **+63-2-842-7951**