


## Product Bulletin

Product  
Name

### STEPANTEX® SP-90

Chemical  
Structure



CAS Registry  
Number

91995-81-2

INCI Name

Dialkylester Ammonium Methosulfate

Applications

STEPANTEX SP-90 is a cationic surfactant ideal for producing fabric softeners and textile softening auxiliaries. This product can be used in household and institutional products. It can produce finished goods from regular to concentrates, with solids ranging from 3% to 20%. STEPANTEX SP-90 is sourced from vegetable-based feedstock and provides the following benefits: good softening, good antistatic properties, very good rewetting, and is non-yellowing on clothing.

Typical  
Properties

Appearance at 25°C ..... Pale yellow creamy paste  
pH, 5% in water ..... 3.30  
Solids, % by wt. .... 90  
Actives, meq/g ..... 1.08  
Color, Gardner ..... 2  
Pour Point, °C (°F) ..... 29 (84)  
Minimum Handling Temperature (MHT), °C (°F) ..... 40 (104)  
Flash Point, °C (°F) ..... <37 (<99)  
Viscosity at MHT, cps ..... 370

Environmental  
Effects

STEPANTEX SP-90 is readily biodegradable.

Preservative  
Compatibility

Preservatives that are cationic compatible and are stable and effective at a pH between 2.5 and 4.5 should be compatible with STEPANTEX SP-90. Among isothiazolinone derivative preservatives, STEPANTEX SP-90 is only compatible with BIT.

Storage &  
Handling

Standard Packaging: STEPANTEX SP-90 is available in drum and in bulk quantities.

STEPANTEX SP-90 should be stored in stainless steel storage tanks preferably of type 316L. Tanks should be padded with a nitrogen gas blanket and equipped with conservation vents and flame arrestors. Tanks should be adequately insulated to maintain elevated temperatures. Generally, mixing is recommended to maintain homogeneity, either by a mechanical stirrer or re-circulation loop.

The color and odor of STEPANTEX SP-90 fabric softener quaternaries are susceptible to degradation as a result of exposure to high temperatures, particularly in the presence of air.



Storage facilities should be designed to maintain a minimum product temperature of 45°C (113°F) and a maximum temperature of 60°C (140°F). Avoid overheating or freezing.

Hot water heating provided through No. 316L stainless steel heating coils is recommended. Steam heating through coils can be used. No. 316L stainless steel centrifugal or positive displacement pumps should be used. Piping should be of No. 316L stainless steel, Schedule 40 or Steel Kynar lined P.V.F. Rubber hoses lined with Teflon or cross-linked polyethylene and equipped with No. 316L stainless steel fittings are recommended for loading and unloading.

Handle STEPANTEX SP-90 with care. It is recommended that STEPANTEX SP-90 be stored in sealed containers kept in a well-ventilated area away from sparks, fire, and open flame. Avoid overheating or freezing. Equipment should be grounded when transferring or using material. Normal safety precautions (i.e., gloves and safety goggles) should be employed when handling STEPANTEX SP-90. Contact with eyes, nose or prolonged contact with skin should be avoided. Wash thoroughly after handling STEPANTEX SP-90.

**Workplace  
Exposure**

Occupational exposure can occur primarily through skin contact or via inhalation of vapors and mists. Engineering controls, personal protective equipment, and other workplace practices should be used to control these exposures. See SDS for more information.

**Clearances**

The international inventories (country clearances) of STEPANTEX SP-90 can be found in Section 15 of the Safety Data Sheet (SDS). It is the responsibility of the formulator to review the chemical control regulations for each country where the end-product is intended to be sold or used. If you have any further questions regarding inventories, please contact North America Technical Service at techserv@stepan.com.

**Product  
Stewardship**

This product bulletin has been written in accordance with ACC's Product Stewardship guidelines.

**Additional  
Safety  
Information**

A Safety Data Sheet (SDS) is available upon request.



The information contained herein is based on the manufacturer's own study and the works of others and is subject to change without prior notice. The information is not intended to be all-inclusive, including as to the manner and conditions of use, handling, storage or disposal or other factors that may involve additional legal, environmental, safety or performance considerations. Nothing contained herein grants or extends a license, express or implied, in connection with any patents issued or pending of the manufacturer or others, nor shall be construed as a recommendation to infringe any patents. STEPAN COMPANY MAKES NO PRODUCT WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR USE, EXPRESS OR IMPLIED, AND NO OTHER WARRANTY OR GUARANTY, EXPRESS OR IMPLIED, IS MADE, INCLUDING AS TO INFORMATION REGARDING PERFORMANCE, SAFETY, SUITABILITY, STABILITY, ACCURACY, COMPLETENESS, OR ADEQUACY. Stepan Company (and its employees, subsidiaries and affiliates) shall not be liable (regardless of fault) to the vendee, its employees, or any other party for any direct, indirect, special, or consequential damages arising out of or in connection with the information provided herein, including in respect of its accuracy, completeness, adequacy, furnishing, use, or reliance upon such information. The vendee assumes and releases Stepan Company (and its employees, subsidiaries and affiliates) from all liability, whether in tort, contract or otherwise to the fullest extent possible under the relevant law.

**Stepan**   
**Corporate Headquarters**  
**Northfield, Illinois 60093, U.S.A.**  
**Phone: 847-446-7500**  
**Fax: 874-501-2100**  
**Website: [www.stepan.com](http://www.stepan.com)**

For Technical Service Call:  
Stepan North America **+1-800-745-7837**  
Stepan Mexico **+55-11-5089-2208**  
Stepan Quimica **+55-11-5089-2200**  
Stepan Colombia **+571-636-2808**  
Stepan Europe **+33-476-505-160**  
Stepan Asia **+656-879-9855**  
Stepan Philippines **+656-879-9855**

For Customer Service Call:  
Stepan North America **+1-800-457-7673**  
Stepan Mexico **+52-555-533-1967**  
Stepan Quimica **+55-11-5089-2200**  
Stepan Colombia **+57-6-8993125**  
Stepan UK **+44-161-338-5511**  
Stepan France **+33-476-50-51-00**  
Stepan Philippines **+63-2-842-7951**