Stepan 💃

SAFETY DATA SHEET

1. Identification

Product identifier TOXIMUL 3476F

Other means of identification

Product code 1514

Recommended use Surfactant

Recommended restrictions For industrial use only. **Manufacturer/Importer/Supplier/Distributor information**

Manufacturer

Company name Stepan Company
Address 22 West Frontage Road
Northfield, IL 60093

USA

Telephone General 1-847-446-7500

E-mail Not available.

Emergency phone number Medical 1-800-228-5635

Chemtrec 1-800-424-9300 Chemtrec Int'l +1 703-527-3887

2. Hazard(s) identification

Physical hazardsFlammable liquidsCategory 4Health hazardsAcute toxicity, oralCategory 4Skin corrosion/irritationCategory 2Serious eye damage/eye irritationCategory 2ACarcinogenicityCategory 2Environmental hazardsHazardous to the aquatic environment, acuteCategory 2

hazard

Hazardous to the aquatic environment,

long-term hazard

OSHA defined hazards Not classified.

Label elements





Signal word Warning

Hazard statement Combustible liquid. Harmful if swallowed. Causes skin irritation. Causes serious eye irritation. Suspected of causing cancer. Toxic to aquatic life. Harmful to aquatic life with long lasting effects.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Wash thoroughly after handling. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection. Do not eat, drink or smoke when using this product.

Category 3

Response If on skin: Wash with plenty of water. If in eyes: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.

Rinse mouth. Specific treatment (see this label). If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated

clothing and wash before reuse. In case of fire: Use appropriate media to extinguish.

Storage Store in a well-ventilated place. Keep cool. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Material name: TOXIMUL 3476F

Material ID: 5951 Product code: 1514 Version #: 02 Revision date: 08-22-2018 Print date: 08-22-2018

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Anionic/nonionic detergent blend*		Proprietary*	60 - 80
_Solvent naphtha, petroleum, heavy arom.		64742-94-5	10 - < 20
1-hexanol		111-27-3	5 - < 10
Naphthalene		91-20-3	1 - < 3

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON

CENTER or doctor/physician if you feel unwell.

Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Take off Skin contact

contaminated clothing and wash before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Rinse mouth. Get medical attention if symptoms occur. Ingestion

Most important

symptoms/effects, acute and

delayed

Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. May cause redness and pain.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation.

Symptoms may be delayed.

General information

IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

The product is combustible, and heating may generate vapors which may form explosive vapor/air mixtures. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards Combustible liquid.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Avoid inhalation of vapors or mists. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained.

Material name: TOXIMUL 3476F SDS US

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. This product is miscible in water.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent product from entering drains. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use.

Environmental precautions

Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from open flames, hot surfaces and sources of ignition. When using do not smoke. Avoid breathing mist or vapor. Avoid contact with skin. Avoid contact with eyes. Avoid prolonged exposure. Avoid contact with clothing. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. Avoid release to the environment. Do not empty into drains.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Store in original tightly closed container. Store in a cool, dry place out of direct sunlight. Store in a well-ventilated place. Keep in an area equipped with sprinklers.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)					
Components	Туре	Value			
Naphthalene (CAS 91-20-3)	PEL	50 mg/m3			
		10 ppm			
US. ACGIH Threshold Limit Values	•				
Components	Туре	Value			
Naphthalene (CAS 91-20-3)	TWA	10 ppm			
US. NIOSH: Pocket Guide to Chem	ical Hazards				
Components	Туре	Value			
Naphthalene (CAS 91-20-3)	STEL	75 mg/m3			
		15 ppm			
	TWA	50 mg/m3			
		10 ppm			
US. Workplace Environmental Exp	osure Level (WEEL) Guides				
Components	Туре	Value	Form		
1-hexanol (CAS 111-27-3)	TWA	40 ppm			
Propylene Glycol (CAS	TWA	10 mg/m3	Aerosol.		

Biological limit values

No biological exposure limits noted for the ingredient(s).

Exposure guidelines

57-55-6)

US - California OELs: Skin designation

Naphthalene (CAS 91-20-3)

Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

Naphthalene (CAS 91-20-3)

Can be absorbed through the skin.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Material name: TOXIMUL 3476F

SDS US

Skin protection

Hand protection Wear appropriate chemical resistant gloves.Other Wear appropriate chemical resistant clothing.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment. If engineering controls do

not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved

respirator must be worn.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work

clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Liquid.

Form Not available.
Color Amber.
Odor Not available.

Odor threshold

PH

Not available.

Not available.

Not available.

Not available.

Not available.

Initial boiling point and boiling

range

> 201 °F (> 93.89 °C)

Flash point 157.0 °F (69.4 °C) Setaflash

Evaporation rate

Flammability (solid, gas)

Upper/lower flammability or explosive limits

Explosive limit - lower (%)

Explosive limit - upper (%)

Vapor pressure

Not available.

Not available.

Relative density

Not available. Not available.

Solubility(ies)

Vapor density

Solubility (water)

Auto-ignition temperature

Decomposition temperature

Viscosity

Not available.

Not available.

3990 cP @ 25C

Other information

Percent volatile 20 %

 Pour point
 26 °F (-3.33 °C)

 Specific gravity
 1.06 @ 25C

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

Material name: TOXIMUL 3476F

Material ID: 5951 Product code: 1514 Version #: 02 Revision date: 08-22-2018 Print date: 08-22-2018

11. Toxicological information

Information on likely routes of exposure

Prolonged inhalation may be harmful. Inhalation

Causes skin irritation. Skin contact

Causes serious eye irritation. Eye contact

Harmful if swallowed. Expected to be a low ingestion hazard. Ingestion

Symptoms related to the physical, chemical and toxicological characteristics Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May

cause redness and pain.

Information on toxicological effects

Acute toxicity Harmful if swallowed. Expected to be a low hazard for usual industrial or commercial handling by

trained personnel.

Test Results Components **Species**

Naphthalene (CAS 91-20-3)

Acute

Dermal

LD50 Rabbit > 2 g/kg

Oral

LD50 Rat 490 mg/kg

Skin corrosion/irritation Causes skin irritation.

Serious eve damage/eve

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not available.

This product is not expected to cause skin sensitization. Skin sensitization

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Suspected of causing cancer. Carcinogenicity

IARC Monographs. Overall Evaluation of Carcinogenicity

Naphthalene (CAS 91-20-3) 2B Possibly carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Naphthalene (CAS 91-20-3) Reasonably Anticipated to be a Human Carcinogen.

This product is not expected to cause reproductive or developmental effects. Reproductive toxicity

Specific target organ toxicity -

single exposure

Not applicable.

Specific target organ toxicity -

repeated exposure

Not applicable.

Aspiration hazard

Not applicable.

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity Toxic to aquatic life. Harmful to aquatic life with long lasting effects.

Persistence and degradability Expected to be inherently biodegradable.

No data available. Bioaccumulative potential Partition coefficient n-octanol / water (log Kow)

Propylene Glycol -0.92

Mobility in soil No data available.

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation Other adverse effects

potential, endocrine disruption, global warming potential) are expected from this component.

Material ID: 5951 Product code: 1514 Version #: 02 Revision date: 08-22-2018 Print date: 08-22-2018

13. Disposal considerations

Disposal instructionsDispose of contents/container in accordance with local/regional/national/international regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

UN number UN3082

UN proper shipping name Transport hazard class(es) Combustible Liquid, N.O.S. (Aromatic Naphtha, Hexanol; Naphthalene RQ = 6803 LBS)

Class 9
Subsidiary risk Packing group III

Special precautions for user Not available.

IATA

UN number UN3082

UN proper shipping name Transport hazard class(es) RQ, Environmentally hazardous substance, liquid, N.O.S. (Naphthalene)

Class 9
Subsidiary risk Packing group III
Environmental hazards No.

Special precautions for user Not available.

IMDG

UN number UN3082

UN proper shipping name Transport hazard class(es) RQ, Environmentally Hazardous Substance, Liquid, N.O.S. (Naphthalene)

Class 9
Subsidiary risk Packing group III

Environmental hazards

Marine pollutant No.

EmS Not available.


Special precautions for user Not available.

Transport in bulk according to Not available.

Annex II of MARPOL 73/78 and

the IBC Code

DOT; IATA; IMDG



15. Regulatory information

US federal regulationsThis product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

Material name: TOXIMUL 3476F

CERCLA Hazardous Substance List (40 CFR 302.4)

Naphthalene (CAS 91-20-3)

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Yes

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

chemical

Classified hazard categories

Flammable (gases, aerosols, liquids, or solids)

Listed.

Acute toxicity (any route of exposure)

Skin corrosion or irritation

Serious eye damage or eye irritation

Carcinogenicity

SARA 313 (TRI reporting)

Chemical name CAS number % by wt. Naphthalene 91-20-3

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Naphthalene (CAS 91-20-3)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Hazardous substance

Not regulated.

Clean Water Act (CWA)

Section 112(r) (40 CFR

68.130)

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

California Proposition 65

WARNING: This product can expose you to chemicals including acetaldehyde, which are known to the State of

California to cause cancer, and ethylene glycol, which are known to the State of California to

cause birth defects or other reproductive harm. For more information go

to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

1,4-dioxane (CAS 123-91-1) Listed: January 1, 1988 Acetaldehyde (CAS 75-07-0) Listed: April 1, 1988 Listed: July 1, 1987 Ethylene oxide (CAS 75-21-8) Naphthalene (CAS 91-20-3) Listed: April 19, 2002 Propylene oxide (CAS 75-56-9) Listed: October 1, 1988

California Proposition 65 - CRT: Listed date/Developmental toxin

Ethylene Glycol (CAS 107-21-1) Listed: June 19, 2015 Ethylene oxide (CAS 75-21-8) Listed: August 7, 2009

California Proposition 65 - CRT: Listed date/Female reproductive toxin

Ethylene oxide (CAS 75-21-8) Listed: February 27, 1987

California Proposition 65 - CRT: Listed date/Male reproductive toxin

Ethylene oxide (CAS 75-21-8) Listed: August 7, 2009

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Naphthalene (CAS 91-20-3)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes

Material name: TOXIMUL 3476F

Country(s) or regionInventory nameOn inventory (yes/no)*JapanInventory of Existing and New Chemical Substances (ENCS)NoKoreaExisting Chemicals List (ECL)YesNew ZealandNew Zealand Inventory (NZIoC)YesPhilippinesPhilippine Inventory of Chemicals and Chemical SubstancesYes

(PICCS)

Taiwan Taiwan Inventory (TCSI)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

Yes

16. Other information, including date of preparation or last revision

 Issue date
 03-11-2015

 Revision date
 08-22-2018

Version # 02

Disclaimer

Terms and Conditions. This SDS is designed only as guidance for the products to which it applies. To the greatest extent permitted by applicable law, nothing contained herein creates any legal obligation including contractual obligations, expressed or implied warranties, including any warranties of merchantibility or fitness for particular purpose; or confers any intellectual property rights, including rights to use trademarks or a license to use patents, issued or pending. The information contained herein is based on the manufacturer's own study and the work of others, and is subject to change at any time without further notice. There is no warranty, expressed or implied, as to the accuracy, completeness or adequacy of the information contained herein, and neither the provider nor the manufacturer (nor the agents, directors, officers, contractors or employees of either) are liable to any party for any damages of any nature, including direct, special or

consequential damages arising out of or in connection with the accuracy, completeness, adequacy or furnishing of any information in this SDS, or in any other way related (directly or indirectly) to this SDS. The receipt and use of this information constitutes consent to these terms and conditions.

Revision information This document has undergone significant changes and should be reviewed in its entirety.

Material name: TOXIMUL 3476F SDS US

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).