

Name	POWDER CONCENTRATE KITCHEN CLEANER		
No.	1449		
Description	This naturally derived powder formulation can be diluted 1:91 with tap water and be used as a kitchen cleaner.		
Formulation	INGREDIENTS:	<u>% by Weight</u>	<u>Functionality</u>
	=== Phase 1 === Maltrin® M700 Maltodextrin (Grain Processing Corp.)** BIO-SOFT® EC-639	-	Filler Surfactant
	=== Phase 2 === AMPHOSOL® LB-DRY STEPANOL® WA-100 NF/USP Sodium Gluconate (TCI America) Sodium Metasilicate Pentahydrate Sodium Citrate	15 10 7	Surfactant Surfactant Builder Builder Builder
	Total	100	
Procedure	 Charge Maltrin® M700 Maltodextrin into appropriately sized container. While mixing, add BIO-SOFT® EC-639. While mixing, add remaining materials one at a time. **Note: Maltrin® M700 Maltodextrin supplied by Grain Processing Corp. is Maltodextrin. 		
Physical Properties	Appearance, as is pH (1:91 diluttion ratio) Viscosity at 25ºC (1:91 dilution ratio), cps	Powder 10.0 - 11.0 Water thin	
Storage/ Stability	4 weeks at 60% relative humidity (as is) 4 weeks at 5°C (1:91 dilution ratio) 4 weeks at 25°C (1:91 dilution ratio) 4 weeks at 40°C (1:91 dilution ratio) 4 weeks at 50°C (1:91 dilution ratio)	Stable Stable Stable Stable Stable	
Instructions for Use	Make a 1.1% by solution with tap water (this is a 1:91 dilution ratio) by taking 1.1% by weight of the powder and dissolving it in 98.9% by weight of tap water. Mix until incorporated. Apply to surface using a spray bottle and wipe.		
	1:91 dilution is comparable to benchmarks that when evaluated using Stepan Method SM250-D Kitchen Spray Test.		
External Comment	Marketing Notes: BCI = 79. Total Biorenewable Carbon Index (BCI) was calculated for the Stepan surfactants and other ingredients used in this formulation. For further information on Stepan's BCI, visit www.stepan.com. As of March 2022, AMPHOSOL LB-DRY is not commercially available yet. Contact your Stepan Representative for more information."		
Registered	AMPHOSOL®		

Trademarks BIO-SOFT® of Stepan Company

For Additional Assistance For applications or product handling assistance, call our Technical Service Department at 1-800-745-7837 (U.S.) or +33 476 505 100 (Europe).

For ordering assistance, call our Account Service Department at 1-800-457-7673.

The information contained herein is based on the manufacturer's own study and the works of others and is subject to change without prior notice. The information is not intended to be all-inclusive, including as to the manner and conditions of use, handling, storage or disposal or other factors that may involve additional legal, environmental, safety or performance considerations. Nothing contained herein grants or extends a license, express or implied, in connection with any patents issued or pending of the manufacturer or others, or shall be construed as a recommendation to infringe any patents. STEPAN COMPANY MAKES NO PRODUCT WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR USE, EXPRESS OR IMPLIED, AND NO OTHER WARRANTY OR GUARANTY, EXPRESS OR IMPLIED, IS MADE, INCLUDING AS TO INFORMATION REGARDING PERFORMANCE, SAFETY, SUITABILITY, STABILITY, ACCURACY, COMPLETENESS, OR ADEQUACY. Stepan Company (and its employees, subsidiaries and affiliates) shall not be liable (regardless of fault) to the vendee, its employees, or any other party for any direct, indirect, special or consequential damages arising out of or in connection with the accuracy, completeness, adequacy, furnishing, use, or reliance upon information provided herein. The vendee assumes and releases Stepan Company (and its employees, subsidiaries and affiliates) from all liability, whether in tort, contract or otherwise to the fullest extent possible under the relevant law.



Stepan Company Northbrook, Illinois 60062 Telephone (847) 446-7500

Revision Date: 03/18/2022 Publication Date: 03/18/2022 © 2022, Stepan Company. All rights reserved.